

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 (currently amended). A counterflow heat exchanger comprising a plurality ~~one or more~~ cold air intake passageways and a plurality ~~one or more~~ hot air intake passageways wherein the flow of cold air is opposite the flow of hot air and wherein each cold air intake passageway contacts at least one hot air intake passage way and wherein said cold air is released from said heat exchanger from a plurality of cold air exits and said hot air is released from said heat exchanger from a plurality of hot air exits.

2 (original). The heat exchanger according to claim 1 wherein each hot air intake passageway has an upper surface and a lower surface and at least one hot air intake passageway has a cold air intake passageway in contact with each of said upper and lower surfaces.

3 (original). The heat exchanger according to claim 2 wherein each hot air intake passageway has a pair of opposing sidewalls connecting said upper and lower surfaces.

4 (original). The heat exchanger according to claim 3 wherein each of said upper and lower surfaces have a surface area greater than the surface area of each of said sidewalls.

RECEIVED

FEB 27 2004

TECHNOLOGY CENTER R3700



5 (currently amended). The heat exchanger according to claim [[5]] 4 wherein each of said hot air passageway exhausts the air exiting said passageway perpendicular to the flow of cold air in the cold air intake passageways.

6 (original). The heat exchanger according to claim 2 wherein said passageways are formed from a corrugated fin.

7 (original). The heat exchanger according to claim 6 wherein the corrugated fin forming said passageways forms three sides of said passageways.


8 (original). The heat exchanger according to claim 7 wherein said passageways have a fourth side formed from a heat exchanger sidewall.

9 (original). The heat exchanger according to claim 2 further comprising a split manifold.

10 (currently amended) . A counterflow heat exchanger comprising cold air intake passageways and hot air intake passageways wherein the flow of cold air is opposite the flow of hot air and wherein each cold air intake passageway contacts at least one hot air intake passage way;

wherein each hot air intake passageway has an upper surface and a lower surface and at least one hot air intake passageway has a cold air intake passageway in contact with each of said upper and lower surfaces;

RECEIVED
FEB 27 2004
TECHNOLOGY CENTER R3700



~~The heat exchanger according to claim 9 wherein there is a split manifold, said~~
the split manifold ~~[[comprises]]~~ comprising a plurality of entranceways and exits, each said entranceways having an intake passage extending therefrom and each of said exits having an outflow passage extending therefrom, said intake passage splitting into two or more intake sections and each of said outflow passages splitting into two or more outflow sections.

11 (original). The heat exchanger according to claim 10 wherein one or more outflow sections have a top surface and a bottom surface and there is a intake section on each of said surfaces and wherein one or more intake sections have a top surface and a bottom surface and there is a outflow section on each of said surfaces.

12 (currently amended). The heat exchanger according to claim 1 wherein the ~~aspect ratio of the height of the corrugated fin to the width of the corrugated fin~~ is at least 10:1.
~~invention has a high aspect ratio for the corrugated fin compared to the prior art.~~

13 (original). The heat exchanger according to claim 1 wherein the conduction losses associated with a long effective fin in a multi-stage design are eliminated.

14 (original). The heat exchanger according to claim 1 wherein fin efficiency approaches unity.

15 (original). The heat exchanger according to claim 1 wherein fin efficiency approaches 100%.

16 (original). The heat exchanger according to claim 14 wherein the conductive heat transfer losses are eliminated.

RECEIVED
FEB 27 2004
TECHNOLOGY CENTER R3700



17 (original). The heat exchanger according to claim 15 wherein the conductive heat transfer losses are eliminated.

18. (new) A counterflow heat exchanger comprising cold air intake passageways and hot air intake passageways wherein the flow of cold air is opposite the flow of hot air and wherein each cold air intake passageway contacts at least one hot air intake passage way and wherein said cold air is released from said heat exchanger from a plurality of cold air exits and said hot air is released from said heat exchanger from a plurality of hot air exits;

wherein said heat exchanger further comprising a split manifold;

wherein the split manifold comprises a plurality of entranceways and exits, each said entranceways having an intake passage extending therefrom and each of said exits having an outflow passage extending therefrom, said intake passage splitting into two or more intake sections and each of said outflow passages splitting into two or more outflow sections.

19 (new). A counterflow heat exchanger comprising a plurality of cold air intake passageways and a plurality of hot air intake passageways wherein the flow of cold air is opposite the flow of hot air and wherein each cold air intake passageway contacts at least one hot air intake passageway and wherein said cold air is released from said heat exchanger from a plurality of cold air exits and said hot air is released from said heat exchanger from a plurality of hot air exits, said heat exchanger providing cool air for cooling electronic equipment.

RECEIVED

FEB 27 2004

TECHNOLOGY CENTER R3700